

KP-300-777

SPECIFICATION SHEET

NanoSmart[®] SERIES KPMF HC610-MP-PP Water Filtration

Single Manifold Part #:

Replacement Cartridge: KPMF HC610-MP-PP	
· 14″ ·	
	19
<image/> <image/>	

APPLICATIONS





Juice



water

- 1 Carbonator
- Volume: Low-Medium

DESIGNED TO

- Improve taste of fountain beverages
- Provide clean ingredient water to your operations
- NanoSmart[®] technology helps to reduce undesirable impurities including cyst, bacteria, and pathogens, delivering exceptional water quality
- Reduce chlorine, undesirable taste and odor, class 1 particulates, sediment, and scale formation

PERFORMANCE

Chlorine Capacity	50,000 gal @ 4 GPM
Scale Reduction	Up to 50,000 gal @ 4 GPM
Micron Rating	1
Min./Max. Pressure	40 - 100 psi
Min./Max. Temp.	40°- 100°F
Inlet/Outlet Size	3/4" FNPT
Shipping Weight	15 lb
Dimensions (W/D/H)	14" x 9" x 19"

Performance may vary based on local water conditions EPA Est. No. 92879-GA-1

FEATURES & BENEFITS

- 100% activated, hollow carbon with no binding agent delivering high capacities and flow rates with minimal pressure drop
- NanoSmart technology utilizes electro-adsorptive material designed to help reduce undesirable contaminants and chemicals
- Time released polyphosphate increases protection of equipment from scale build up
- Engineered polymer construction for high durability and extended service life
- Modular design allows for easy capacity expansion
- Certified by NSF for microplastic reduction. These refer to small pieces of plastic from packaging, microbeads, plastic bottles, bags, and more



1.800.321.5022 www.KineticoPRO.com WaterCare@KineticoPRO.com NSF.

System Tested and Certified by NSF International against NSF/ANSI Standards 42 for reduction of Chlorine, Taste and Odor, Particulate Reduction, Class I (0.5-1.0 micron), NSF/ANSI Standard 401 for the reduction of Microplastics, and CSA Standard B483.1.