

KP-300-777

NanoSmart[®]SERIES KPMF HC620-MP Water Filtration

Single Manifold Part #:

Replacement Cartridge:	KPMF HC620-MP	
· 14"		
		29"
<image/> <image/> <image/> <text><text><text><text><text><text></text></text></text></text></text></text>		

APPLICATIONS







water

SHEET

• 1 to 2 Carbonator

• Volume: High

DESIGNED TO

- Improve taste of fountain beverages
- Provide clean ingredient water to your operations
- NanoSmart[®] technology helps to reduce undesirable impurities including cyst, bacteria, and pathogens, delivering exceptional water quality
- Reduce chlorine, chloramine*, undesirable taste & odor, class 1 particulates and sediment

PERFORMANCE

Chlorine Capacity	100,000 gal @ 8 GPM
Chloramine Capacity	20,000 gal @ 1.7 GPM*
Micron Rating	1
Min./Max. Pressure	40-100 psi
Min./Max. Temp.	40°- 100°F
Inlet/Outlet Size	3/4" FNPT
Shipping Weight	17 lb
Dimensions (W/D/H)	14" x 9" x 29"

Performance may vary based on local water conditions EPA Est. No. 92879-GA-1

* Tested by 3rd party laboratory to the NSF/ANSI Standard 42

FEATURES & BENEFITS

- 100% activated, hollow carbon with no binding agent delivering high capacities and flow rates with minimal pressure drop
- NanoSmart technology utilizes electro-adsorptive material designed to help reduce undesirable contaminants and chemicals
- Turbo Flow technology evenly distributes water flow and helps to reduce plugging
- Engineered polymer construction for high durability and extended service life
- Modular design allows for easy capacity expansion
- Certified by NSF for microplastic reduction. These refer to small pieces of plastic from packaging, clothing, microbeads, and more



1.800.321.5022 www.KineticoPRO.com WaterCare@KineticoPRO.com System Tested and Certified by NSF International against NSF/ANSI Standards 42 for reduction of Chlorine, Taste and Odor, Particulate Reduction, Class I (0.5-1.0 micron), NSF/ANSI Standard 401 for the reduction of Microplastics, and CSA Standard B4831



SPECIFICATION