

# CoffeePRO SERIES

## KPMF CP614-PP

### Water Filtration

Single Manifold Part #: **KP-300-777**  
Replacement Cartridge: **KPMF CP614-PP**



## APPLICATIONS



Coffee/Tea



Espresso/  
Cappuccino

- Volume: Medium
- Optimal for Multi-Brewer

## DESIGNED TO

- Improve taste, aroma, & clarity of brewed beverages
- Maintain recipe compliance and deliver a consistent beverage experience
- Reduce scale formation and pitting to prolong equipment life
- Remove disinfectants and contaminants, providing high quality ingredient water

## PERFORMANCE

Chlorine Capacity	<b>75,000 gal @ 7gpm</b>
Chloramine Capacity	<b>14,700 gal @ 1.7gpm*</b>
Scale Reduction	<b>Up to 75,000 gal @ 7gpm</b>
Min./Max. Pressure	<b>40 - 100 psi</b>
Min./Max. Temp.	<b>40°- 100°F</b>
Inlet/Outlet Size	<b>3/4" FNPT</b>
Shipping Weight	<b>17 lb</b>
Dimensions (W/D/H)	<b>14" x 9" x 23"</b>

Performance may vary based on local water conditions

\*Tested by 3rd party laboratory to the NSF/ANSI Standard 42

## FEATURES & BENEFITS

- Activated hollow carbon with NO binding agent delivers high capacities, high flow rates, and minimal pressure drop
- Engineered polymer construction for high durability and extended service life
- Modular design allows for easy capacity expansion
- Time released polyphosphate increases protection of equipment from scale build up
- Certified by NSF for microplastic reduction. These refer to small pieces of plastic from packaging, microbeads, plastic bottles, bags, and more



System Tested and Certified by NSF International against NSF/ANSI Standards 42 for reduction of Chlorine, Taste and Odor, Particulate Reduction, Class I (0.5-1.0 micron), NSF/ANSI Standard 401 for the reduction of Microplastics, and CSA Standard B483.1.