

SPECIFICATION SHEET

HPF SERIES HC416-PP Water Filtration

Single Manifold Part #:KP-300-651Replacement Cartridge:HPF HC416-PP



APPLICATIONS





Coffee/Tea



Steamers/ Combi-oven

Espresso/ Cappuccino

Ice Machine

• Volume: Low-Medium

DESIGNED TO

- Improve taste, aroma, & clarity of brewed beverages while reducing contaminants and inhibiting scale build up
- Maintain recipe compliance and deliver a consistent beverage experience
- Reduce scale formation and pitting to prolong equipment life
- Reduce chlorine, undesirable taste & odor, class 1 particulates and sediment

PERFORMANCE

Chlorine Capacity	40,000 gal @ 2.5 gpm
Scale Reduction	Up to 40,000 gal @ 2.5 gpm
Min./Max. Pressure	20 - 125 psi
Min./Max. Temp.	40°- 100°F
Inlet/Outlet Size	3/4" FNPT
Shipping Weight	4 lb
Dimensions (W/D/H)	10" x 5.5" x 19.5"

Performance may vary based on local water conditions

FEATURES & BENEFITS

- Activated hollow carbon with no binding agent delivers high capacities, high flow rates, and minimal pressure drop in a compact solution
- Engineered polymer construction for high durability and extended service life
- Modular design allows for easy capacity expansion
- Time released polyphosphate increases protection of equipment from scale build up
- Certified by NSF for microplastic reduction. These refer to small pieces of plastic from packaging, microbeads, plastic bottles, bags, and more



System Tested and Certified by NSF International against NSF/ANSI Standards 42 for reduction of Chlorine, Taste and Odor, Particulate Reduction, Class I (0.5-1.0 micron), NSF/ANSI Standard 401 for the reduction of Microplastics, and CSA Standard B483.1.



1.800.321.5022 www.KineticoPRO.com WaterCare@KineticoPRO.com

©2025 Kinetico Incorporated. All Rights Reserved. Kinetico Incorporated. 3980 Lakefield Ct. Suwanee, GA 30024 Made in U.S.A. SSHC416-PP_1 01/25