

HC SERIES

KPMF HC610

Water Filtration

Single Manifold Part #: **KP-300-777**

Replacement Cartridge: **KPMF HC610**

System Part #: **KP-SYS-HC610**

14"



19"

APPLICATIONS



Fountain



Coffee/Tea



Juice



Drinking water

- 1 Carbonator
- Volume: Low-Medium

DESIGNED TO

- Improve taste of fountain beverages
- Provide clean ingredient water to your operations
- Reduce chlorine, chloramine*, taste & odor, class 1 particulates, and sediment.

PERFORMANCE

Chlorine Capacity	50,000 gal @ 5GPM
Chloramine Capacity	7,150 gal @ 1.7GPM*
Min./Max. Pressure	40 - 100 psi
Min./Max. Temp.	40°- 100°F
Inlet/Outlet Size	3/4" FNPT
Shipping Weight	13 lb
Dimensions (W/D/H)	14" x 9" x 19"

Performance may vary based on local water conditions

*Tested by 3rd party laboratory to the NSF/ANSI 42 Standard

FEATURES & BENEFITS

- 100% activated Hollow Carbon media. NO binding agents
- Turbo Flow technology evenly distributes water flow and helps to reduce plugging
- Engineered polymer construction for high durability and extended service life
- Minimal pressure drop allows for high flow rates
- Modular design allows for easy capacity expansion



Tested and certified by NSF International against NSF/ANSI Standard 42 for the reduction of Chlorine, Taste & Odor and Particulate Class I.