

CoffeePRO SERIES

KPMF CP610-PP

Water Filtration

Single Manifold Part #: **KP-300-777**
 Replacement Cartridge: **KPMF CP610-PP**



APPLICATIONS



Coffee/Tea



Espresso/
Cappuccino

- Volume: Low-Medium
- Optimal for Single or Multi-Brewer

DESIGNED TO

- Improve taste, aroma, & clarity of brewed beverages
- Maintain recipe compliance and deliver a consistent beverage experience
- Reduce scale formation and pitting to prolong equipment life
- Remove disinfectants and contaminants, providing high quality ingredient water

PERFORMANCE

| | |
|---------------------|--------------------------------|
| Chlorine Capacity | 50,000 gal @ 5gpm |
| Chloramine Capacity | 7,150 gal @ 1.7gpm* |
| Scale Reduction | Up to 50,000 gal @ 5gpm |
| Min./Max. Pressure | 40 - 100 psi |
| Min./Max. Temp. | 40°- 100°F |
| Inlet/Outlet Size | 3/4" FNPT |
| Shipping Weight | 15 lb |
| Dimensions (W/D/H) | 14" x 9" x 19" |

Performance may vary based on local water conditions

*Tested by 3rd party laboratory to the NSF/ANSI Standard 42

FEATURES & BENEFITS

- Activated hollow carbon with NO binding agent delivers high capacities, high flow rates, and minimal pressure drop
- Engineered polymer construction for high durability and extended service life
- Modular design allows for easy capacity expansion
- Time released polyphosphate increases protection of equipment from scale build up
- Certified by NSF for microplastic reduction. These refer to small pieces of plastic from packaging, microbeads, plastic bottles, bags, and more



System Tested and Certified by NSF International against NSF/ANSI Standards 42 for reduction of Chlorine, Taste and Odor, Particulate Reduction, Class I (0.5-1.0 micron), NSF/ANSI Standard 401 for the reduction of Microplastics, and CSA Standard B483.1.