

NanoSmart[™]SERIES KPMF HC610-MP Water Filtration

Single Manifold Part #: KP-300-777

Replacement Cartridge: KPMF HC610-MP



APPLICATIONS









Fountain

Coffee/Tea

Juice

orinking water

- 1 Carbonator
- Volume: Low-Medium

DESIGNED TO

- Improve taste of fountain beverages
- Provide clean ingredient water to your operations
- NanoSmart® technology helps to reduce undesirable impurities including cyst, bacteria, and pathogens, delivering exceptional water quality
- Reduce chlorine, undesirable taste & odor, class 1 particulates and sediment

PERFORMANCE

19"

Chlorine Capacity	50,000 gal @ 4 GPM
Micron Rating	1
Min./Max. Pressure	40 - 100 psi
Min./Max. Temp.	40°- 100°F
Inlet/Outlet Size	3/4" FNPT
Shipping Weight	13 lb
Dimensions (W/D/H)	14" x 9" x 19"
5 (100

Performance may vary based on local water conditions EPA Est. No. 92879-GA-1

FEATURES & BENEFITS

- 100% activated, hollow carbon with no binding agent delivering high capacities and flow rates with minimal pressure drop
- NanoSmart technology utilizes electro-adsorptive material designed to help reduce undesirable contaminants and chemicals
- Turbo Flow technology evenly distributes water flow and helps to reduce plugging
- Engineered polymer construction for high durability and extended service life
- Modular design allows for easy capacity expansion
- Certified by NSF for microplastic reduction. These refer to small pieces of plastic from packaging, clothing, microbeads, and More!



System Tested and Certified by NSF International against NSF/ANSI Standards 42 for reduction of Chlorine, Taste and Odor, Particulate Reduction, Class I (0.5-1.0 micron), NSF/ANSI Standard 401 for the reduction of Microplastics, and CSA Standard B483.1.

^{*}Tested by 3rd party laboratory to the NSF/ANSI Standard 42